Arosta® 307

TOP FEATURES

- Especially developed for steels difficult to weld, such as armour plates and austenitic high Mn-steels
- Often used as a buffer layer in hardfacing applications
- Weldable on AC and DC+ polarity

CLASSIFICATION

AWS A5.4 EN ISO 3581-A

E307-16 E 18 8 Mn R 12

CURRENT TYPE

AC/DC +

WELDING POSITIONS

All position, except vertical down

Λ	D	D	D	n	v	Λ	LS
н	r	r	п	υ	v.	н	_>

ТÜV	DB
+	+

CHEMICAL COMPOSITION (WEIGHT %), TYPICAL, ALL WELD METAL

С	Mn	Si	Cr	Ni	FN (acc.WRC 1992)
0.09	5.0	0.6	18.5	8.5	0

MECHANICAL PROPERTIES, TYPICAL, ALL WELD METAL

	Condition*	0.2% Proof strength	Tensile strength	Elongation	Impact ISO-V (J)	
	Condition	(MPa)	(MPa)	(%)	+20°C	-60°C
Required: AWS A5.4		not specified	min. 590	min. 30	not specified	
EN ISO		min. 350	min. 500	min. 25	not specified	
Typical values	AW	450	650	35	110	75

AW = As welded

OUTPUT RANGE

Diameter x Length (mm)	Current range (A)
2.5 x 350	70-80
3.2 x 350	90-120
4.0 x 350	110-140

PACKAGING AND AVAILABLE SIZES

Diameter x Length (mm)	Packaging	Pieces / unit	Weight (kg)	ltem number
2.5x350	СВОН	97	2.1	527391-1
3.2x350	CBOX	130	4.4	527407-1
4.0x350	CBOX	86	4.5	527414-1

Arosta® 307-EN-01/07/22



TEST RESULTS

Test results for mechanical properties, deposit or electrode composition and diffusible hydrogen levels were obtained from a weld produced and tested according to prescribed standards, and should not be assumed to be the expected results in a particular application or weldment. Actual results will vary depending on many factors, including, but not limited to, weld procedure, plate chemistry and temperature, weldment design and fabrication methods. Users are cautioned to confirm by qualification testing, or other appropriate means, the suitability of any welding consumable and procedure before use in the intended application

Safety Data Sheets (SDS) are available here:



Subject to Change – The information is accurate to the best of our knowledge at the time of printing. Please refer to <u>www.lincolnelectric.eu</u> for any updated information.

Arosta® 307-EN-01/07/22

